

TITAN[®] COATINGS

APOLLOTX130™ PPF MEMBRANE COATING

INCORPORATES ULTRA ADVANCED MIMETIC ELASTOMER COMPONENTS WHICH OFFER BEST IN CLASS CHEMICAL RESISTANCE WITH OMNIPHOBIC SELF CLEANING PROPERTIES.

Contains our Proprietary Dark Matter Technology® DiamondTech™ variant.



PRECAUTIONS AND MAINTENANCE:

Never allow highly alkaline (ph12+) chemicals to sit or dwell on the surface for extended periods.

Avoid washing/abrasion in the first 7 days.
Maintain every 3-6 months with ULTRA.

Coating Type: PPF & PPS

Durability:

Tested to: ASTM B117, ISO9227
ASTM D4587, ASTM D6577

Main Benefits

Maximises chemical resistance of films which are prone to chemical burns from bird lime and insects. Long lasting omniphobic modified surface and reduced the need for ppf reapplication.

Single layer: Up to 4 years

Dual layer: up to 5 years

Suitability: Gloss/Sateen & Matte films

All paint protection films including first generation and new generation films.

Self healing films

Top coated films

TPU hybrid films

First generation PVC ppf

Tph films

Vinyl

Pps paint protection pray

Ultimate PPF Package

Base- VULCANTX155™

Top - APOLLOTX130™

TECHNICAL DATA:

Thickness: Max 2µm

Thermal Resistance: 600°C

PH Tolerance: 1-14